

freud.

Circular Saw Blades

Kružne testere

Catalogue 2018/19 - Katalog 2018/19



Your productive partner

Vaš pouzdan partner

Premium quality industrial tools for superior efficiency

Industrijski alati vrhunskog kvaliteta za maksimalnu efikasnost



A wide range of top performing products

- An extensive variety of precise and high-tech tools.
- Circular Saw Blades: the biggest manufacturer of high quality saw blades worldwide.
 - Cutterheads and Brazed Cutters: freud sets the highest standard in the wood industry and window tooling.
 - Knives, Spare parts and Accessories: in-house production of all Carbide inserts, unique in the world.
 - Drilling, Routing & CNC Tools: a complete range for all applications.

Široka gama vrhunskih proizvoda


Veliki izbor preciznih i modernih alata.

- Kružne testere: najveći proizvođač visokokvalitetnih testera na svetu.
- Glodala sa izmenjivim i lemljenim pločicama: FREUD postavlja najviše standarde u drvnoj i industriji prozora.
- Pločice, rezervni delovi i dodaci: FREUD je jedinstven u svetu po proizvodnji svih karbidnih elemenata u okviru kuće.
- Alati za CNC: kompletan gama za sve aplikacije.



A wide range of industrial cutting tools.
Široka gama industrijskih alata za rezanje.

GATECH
www.freud.rs



Advanced engineering and technology.
Napredno projektovanje i tehnologija.

High quality solutions for your applications


Engineering competence and manufacturing know-how.

- Customized-to-Order: products to match special production needs.
- Enhanced technologies: Silver I.C.E., Perma-SHIELD, EXrim, ISOprofil, High Speed ISOprofil and Split-Edge.

Visokokvalitetna rešenja za Vaše aplikacije

Stručnost u konstruisanju i proizvodnji.

- Specifični zahtevi: proizvodi po specijalnim zahtevima proizvodnje.
- Napredne tehnologije: Silver I.C.E, Perma-SHIELD, EXrim, ISOprofil, High Speed ISOprofil i Split-Edge.



Worldwide presence.
Prisutnost širom sveta.

Global services wherever you are

A belief in "think global and act local".

- Our worldwide subsidiaries and partners in over 90 countries ensure an extensive service and distribution network.
- Since 2009 freud is part of Bosch group, leveraging the global network of the world leading technology supplier.

Globalna usluga gde god da se nalazite

Verovanje u "misli globalno, radi lokalno".

- Naši agenti i partneri širom sveta u preko 90 zemalja osiguravaju dobru uslugu i distribuciju.
- Od 2009. godine FREUD je deo BOSCH grupe, čineći globalnu mrežu vodećeg svetskog dobavljača tehničkih proizvoda.

Advanced technology

Napredna tehnologija

Innovative solutions to maximize
your investments
Inovativna rešenja
za maksimizaciju Vaših investicija




In-house Tungsten Carbide (HW) production

- TiCo Carbide is a specially formulated, highly compact Titanium Cobalt Carbide, engineered and manufactured in-house by freud.
- Special HW grades are mixed based on application needs and checked according to strict quality criteria.
- Special tooth geometries are developed for perfect cuts.

Proizvodnja Tungsten Karbida (HW) "u kući"

- TiCo Karbid je specijalna formula, visokokompaktna verzija Titanijum Kobalt Karbida, stvorena i proizvedena "u kući" od strane FREUD-a.
- Specijalne klase HW mešaju se po potrebi i proveravaju po striktnim kriterijumima kvaliteta.
- Specijalna geometrija zuba razvijena je da bi se omogućio savršen rez.



Overview of different standard HW grades.
Tablica različitih standardnih HW klasa.


GATECH
www.freud.rs

Multiple sharpenings: super square tooth design

- Tip thickness 30% greater than standard tips.
- Up to 25 sharpenings to extend the product life-time.

Višetruka oštrena: superkvadratni zub

- Debljina vrha 30% veća od standardne.
- Do 25 oštrena i znatno duži radni vek alata.




Supersquare tooth.
Superkvadratni zub.

Maximum durability: tri-metal shock resistant brazing

- freud special tri-metal alloy consists of copper wrapped between layers of silver.
- This solution allows the Carbide tips to withstand extreme impact, for maximum durability.

Maksimalna izdržljivost: trimetalni izuzetno otporan sloj

- FREUD-ov specijalni trimetalni sloj sastoji se od bakra između dva sloja srebra.
- Ovakvo rešenje omogućava da Karbidni vrhovi mogu da podnesu ekstremne uslove i imaju maksimalnu trajnost.



Tri-metal brazing.
Trimetalni sloj.

Superior finishing

Superioran završni rez

A flawless result with no re-work
Besprekoran rezultat od prvog do
poslednjeg reza



Reduced friction: Silver I.C.E. Coating

- A high performing and anticorrosive coating to maintain the blade temperature low during the working process.
- The non-stick feature improves chip ejection and notably reduces resin build-up, significantly reducing friction and extending the life time of the blade.

Smanjeno trenje: Silvet I.C.E. zaštitni sloj

- Antikorozivni zaštitni sloj visokih performansi održava temperaturu testere nižom tokom rada.
- Nelepljivi sloj poboljšava radne karakteristike smanjenjem lepljenja piljevine, značajnim smanjenjem trenja i produžavanjem veka trajanja sečiva.



**Silver I.C.E.
Coating**

Silver I.C.E. coating.
Silver I.C.E. zaštitni sloj


GATECH
www.freud.rs

Improved precision: Anti-vibration slots for the perfect finishing

- Body slots laser cut with freud innovative technology.
- Also available with thermoplastic polyurethane filling, that considerably reduces vibration and minimizes noise.

Poboljšana preciznost: Antivibracioni prorez za savršen rez

- Prorezni na telu testere laserski su usečeni uz pomoć inovativne FREUD-ove tehnologije.
- Prorezni su popunjeni termoplastičnim poliuretanskim materijalom, koji značajno smanjuje vibracije vibracije i buku.



Anti-vibration


Section view of the antivibration slots.
Presek antivibracionih prostate

No blade distortion: laser cut steel, tensioning and balancing

- The high strength laser cut steel extends the blade durability, whereas the tensioning process guarantees maximum precision.
- An automated system balances freud blades one by one, eliminating completely the harmful vibrations.

Nema krivljenja testere: laserski sečen čelik, zategnut i balansiran

- Izuzetno izdržljiv laserski sečen čelik produžava vek trajanja testere, dok proces zatezanja garantuje maksimalnu preciznost.
- Automatizovan sistem balansira sve FREUD testere, eliminirajući potpuno štetne vibracije.



Balancing.
Balansiranje.

Circular saw blades for INDUSTRIAL MACHINES

Kružne testere za INDUSTRISKE MAŠINE

Choose the right tool
Izaberite odgovarajući alat

* LM10 - Only softwood
* LM10 - Samo meko drvo

Suitable for / Odgovarajuće za	Ultimate Najbolja	PERFORMANCE / PERMANSE	
		High Odlična	Good Dobra
Solid wood Masiv	 Multi-rip saw blades for ripping Testere za višelisne cirkulare - uzdužan rez	LM01 - LM10*	LM02-LM03-LM04-LM05-LM06-LM07-LM08
	 Ripping Uzdužan rez	LU1F-LU1G	LU1C-LU1D-LU1E-LU2A-LU2B-LG1C
	 Cross cutting Poprečan rez	LU2A-LU2B-LU2C-LU2D-LU2F	LU2E-LG2C LU1A-LU1E
	 Ripping and cross cutting Uzdužan i poprečan rez		LG2A-LG2B-LU1H LU1B
Laminated Laminati	 Saw blades for cutting laminates Testere za rezanje laminata	LSB X LSB-LU3A-LU3B-LU3C-LU3D-LU3E-LU3F	LG3D
	 Scoring saw blades for laminates Predrezači za laminate	LI13MD-LI13MS-LI14MD-LI14MS-LI16M-LI17M-LI20M-LI22MD-LI22MS-LI25M-LI27M	
Wood composites Drveni kompoziti		LSB X LSB-LU2C-LU2D-LU2E-LU2F-LU3A-LU3B-LU3C-LU3D-LU3F	LU2A-LU2B-LU3E-LG2A-LG2B-LG2C-LG3D LU1E-LU1H
Veneered Furnir		LU3A-LU3B-LU3C-LU3D-LU3E-LU3F	LG3D
Picture frames Ramovi		LU1I-LU1L	
Non ferrous metals Obojeni metali		LU5F LU5A-LU5B-LU5C-LU5D-LU5E	
Ferrous metals Crni metali		LU6A	
Plexiglas Pleksiglas		LU4A-LU4B	
Plastic materials Plastični materijali		LU5F LU4A-LU4B-LU5D-LU5B	LU2C-LU2D-LU2F-LG2C-LU3F
PVC PVC		LU5F	LU5B - LU5D
Solid surfaces Radne ploče		LU4D	

GATECH
www.freud.rs

Circular saw blades for PORTABLE MACHINES

Kružne testere za RUČNE CIRKULARE


Choose the right tool
Izaberite odgovarajući alat

Suitable for / Odgovarajuća za:		PERFORMANCE / PERMANSE		
		Ultimate Najbolja	High Odlična	Good Dobra
Solid wood Masiv	 Ripping Uzdužan rez	LP60M		
	 Cross cutting Poprečan rez	LP40M-LP60M		
	 Ripping and cross cutting Uzdužan i poprečan rez		LP20M-LP30M-LP60M	LP70M
Laminated Laminati	 Saw blades for cutting laminates Testere za rezanje laminata	LP67M	LP85M-LP91M-LP40M	
Wood composites Drveni kompoziti			LP91M	LP40M
Veneered Furnir			LP91M	
Non ferrous metals Obojeni metali		LP80M	LP85M-LP91M-LP40M	
Ferrous metals Crni metali		LP90M	LP91M	
Plexiglas & plastic materials Pleksiglas i plastični materijali			LP91M	
PVC PVC			LP91M	
Solid surfaces Radne ploče			LP91M	

GATECH
www.freud.rs

Teeth shape varieties as applied to saw blades

Vrste zuba po tipovima testera

FLAT TOOTH RAVAN ZUB	DOUBLE TRIPLE CHIP TOOTH DUPLI TRAPEZNI ZUB	CONICAL TOOTH NAIZMENIČAN KOSI ZUB	BEVELLED TOOTH NAIZMENIČAN BW ZUB
LM01 - LM02 - LM05 - LM06 - LM07 - LM08 - LM10 - LU1E - LI20M - LI17M - LT18M - LT20M	LSC - LU4D - LU6A	LI25M	LU1B
			
Suitable for / Odgovarajući za:	Suitable for / Odgovarajući za:	Suitable for / Odgovarajući za:	Suitable for / Odgovarajući za:
 Ripping of softwood Legno tenero lungo vena	 Ferrous metals Metalli ferrosi	 Laminates (scoring saw blades) Laminati (lame incisore)	 Ripping and cross cutting of softwood Legno tenero lungo e traverso vena
 Ripping of hardwood Legno duro lungo vena	 Solid surfaces Materiali polimerici		 Ripping and cross cutting of hardwood Legno duro lungo e traverso vena
			 Chipboard Truciolare
			 Solid wood and composites with nails and impurities Legni e compositi con chiodi o impurità

GATECH
www.freud.rs





FLAT-TRIPLE CHIP TOOTH RAVAN - TRAPEZNI ZUB	INCLINED TOOTH KOSI ZUB	PYRAMID TOOTH PIRAMIDALNI ZUB	AXIAL TOOTH AKSIJALNI ZUB
LU3D - LU3E - LU3F - LG3D - LU4A - LU5A - LU5B - LU5C - LU5D - LU5E - LP40 - LP80 - LP90 - LP85 - LP91	LI22M - LI13M - LI14M - LT16M - LT12M - LT14M	LU5F	LU1L - LU4B
			
Suitable for / Odgovarajući za:	Suitable for / Odgovarajući za:	Suitable for / Odgovarajući za:	Suitable for / Odgovarajući za:
 Laminates / bilaminates Laminati / obostrano oplemenjeni pločasti materijali	 Cross cutting of softwood Poprečno rezanje mekog drveta	 PVC	 Cross cutting of softwood Poprečno rezanje mekog drveta
 Chipboard Iverica	 Cross cutting of hard-wood Poprečno rezanje tvrdog drveta	 Non-ferrous metals Obojeni metali	 Cross cutting of hard-wood Poprečno rezanje tvrdog drveta
 MDF Medijapan (MDF)	 Laminates / bilaminates Laminati / obostrano oplemenjeni pločasti materijali		 Picture frames Ramovi za slike
 Plywood Furnir (šper)	 Plywood Furnir (šper)		 Plexiglas
 Plexiglas Pleksiglas	 Scoring saw blades, for laminates Predrezači, za laminate		 Plastic materials Plastični materijali
 Plastic materials Plastični materijali			
 Non-ferrous metals Obojeni metali			

Teeth shape varieties as applied to saw blades


Vrste zuba po tipovima testera

CONCAVE TOOTH KONKAVNI ZUB	ROUNDED TOOTH ZAOBLJENI ZUB	ALTERNATE TOP BEVEL TOOTH NAIZMENIČNI BW ZUB
LU3B - LU3C	LU1G	LM03 - LM04 - LM08 - LU1A/C/D/F/H/I - LU2A/B/C/D/E/F - LU3A - LG1C - LG2A - LG2B - LG2C - LI16M LI27M - LP20M - LP30M - LP40M - LP60M - LP67M - LP70M
		
Suitable for / \	Suitable for / \	Suitable for / \
 Laminates / bilaminates Laminati / obostrano oplemenjeni pločasti materijali	 Ripping of softwood Uzdužno rezanje mekog drveta	 Ripping and cross cutting of softwood Uzdužno i poprečno rezanje mekog drveta
		 Ripping and cross cutting of hardwood Uzdužno i poprečno rezanje tvrdog drveta
		 Chipboard Iverica
		 MDF Medijapan (MDF)
		 Plywood Furnir (šper)
		 Picture frames Ramovi za slike


GATECH
www.freud.rs

HOOK ANGLES GRUDNI UGOVI	(α) 15° ÷ 25°	(α) 5° ÷ 15°	(α) 0° ÷ 5°	(α) 0° ÷ -10°
				
Suitable for / \	Suitable for / \	Suitable for / \	Suitable for / \	
 Cross cutting of softwood Poprečno rezanje mekog drveta	 Chipboard Iverica	 Chipboard Iverica	 Plexiglas Pleksiglas	
 Cross cutting of hardwood Poprečno rezanje tvrdog drveta	 Plywood Furnir (šper)	 Non-ferrous metals Obojeni metali	 Plastic materials Plastični materijali	
 Solid surfaces Kompaktni materijali (radne ploče)	 Laminates / bilaminates Laminati / obostrano oplemenjeni pločasti materijali	 Ferrous metals Crni metali	 Non-ferrous metals Obojeni metali	
	 PVC		 Laminates / bilaminates Laminati / obostrano oplemenjeni pločasti materijali	

LU1A




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades for radial and pendulum machines TM - Testere za potezne prerezivače

Saw blades suitable for crosscutting.

Machines: Radial, pendulum and portable machines.

Features: ATB 15° tooth with negative cutting angle.

Material: Soft, hard, dried and wet solid wood.

Testere za poprečno rezanje.

Mašine: Potezni prerezivači, prenosni cirkulari.

Oblik zuba: ATB 15° sa negativnim uglom rezanja.

Materijal: Meko i tvrdo drvo, suvo ili vlažno.

FT02: 2/9/46,4 + 2/10/60




FT03: 2/7/42 + 2/10/60

D mm	B mm	b mm	d mm	Z	NL Pomoći otvori	Code Šifra	SAP SAP
300	4,4	3,0	30	36	FT02	LU1A 0100	F03FS04572
350	4,4	3,0	30	42	2/10/60	LU1A 0200	F03FS04573
400	4,4	3,0	30	48	FT02	LU1A 0300	F03FS04574
450	4,4	3,0	30	54	FT03	LU1A 0400	F03FS04575
500	4,8	3,2	30	60	2/10/60	LU1A 0500	F03FS04576
550	4,8	3,2	30	72	2/10/60	LU1A 0600	F03FS04577
600	5,0	3,5	30	72	FT02	LU1A 0700	F03FS04578

GATECH
www.freud.rs

Working with spindle over the workpiece

Mašinska obrada sa osovinom iznad radne površine



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Cross cutting of softwood
Poprečno rezanje mekog drveta
Cross cutting of hardwood
Poprečno rezanje tvrdog drveta

Ultimate
Najbolja

High
Odlična


Good
Dobra




LU1B



HW K10S




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades for carpentry works

TM - Testere za stolarske radove

Saw blades suitable for ripping and crosscutting.

Machines: Table saws, portable machines.

Features: ATB/bevelled tooth with positive cutting angle.

Material: Soft and hard solid wood and panels, even in case of nails or metal clips.

Testere za uzdužno i poprečno rezanje.

Mašine: Stabilni cirkulari, prenosni cirkulari.

Oblik zuba: ATB/smaknuti zub sa pozitivnim uglom rezanja.

Materijal: Meko i tvrdo drvo i drveni paneli, čak i sa prisustvom eksera ili metalnih klamerica.

FT01: 2/7/42 + 2/9/46,4 + 2/10/60


FT02: 2/9/46,4 + 2/10/60

FT03: 2/7/42 + 2/10/60

D mm	B mm	b mm	d mm	Z	NL Pomoći otvori	Code Šifra	SAP SAP
250	3,4	2,2	30	18	FT01	LU1B 0100	F03FS04579
300	3,4	2,2	30	20	FT01	LU1B 0200	F03FS04580
315	3,4	2,2	30	20	FT01	LU1B 0300	F03FS04582
350	3,7	2,5	30	24	FT02	LU1B 0400	F03FS04583
400	4,0	2,8	30	28	2/10/60	LU1B 0500	F03FS04585
450	4,2	3,0	30	32	FT03	LU1B 0600	F03FS04586
500	4,4	3,2	30	36	FT03	LU1B 0700	F03FS04587
550	4,8	3,5	30	44	2/10/60	LU1B 0800	F03FS04588
600	5,2	4,0	30	48	FT03	LU1B 0900	F03FS04589
650	5,6	4,2	30	54	FT02	LU1B 1000	F03FS08324
700	5,6	4,2	30	60	2/10/60	LU1B 1100	F03FS05892

GATECH
www.freud.rs

Cutting height - Visina materijala (mm)




Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.


Ultimate Najbolja	High Odlična	Good Dobra
----------------------	-----------------	---------------

Ripping and cross cutting of softwood
Uzdužno i poprečno rezanje mekog drveta
Ripping and cross cutting of hardwood
Uzdužno i poprečno rezanje tvrdog drveta






Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades to cut solid wood

TM - Testere za rezanje masiva

Saw blades suitable for ripping.

Machines: Table saws, multiripping machines.

Features: ATB 10° tooth with positive cutting angle.

Material: Soft and hard solid wood, also with loose knots.

Testere za uzdužno rezanje.

Mašine: Stabilni cirkulari, višelisni cirkulari.

Oblik zuba: ATB 10° sa pozitivnim uglom rezanja.

Materijal: Meko i tvrdo drvo, može i sa čvorovima.


FT01: 2/7/42 + 2/9/46,4 + 2/10/60

FT02: 2/9/46,4 + 2/10/60

D mm	B mm	b mm	d mm	Z	NL - KN Pomoći otvori	Code Šifra	SAP SAP
250	3,2	2,2	30	22	FT01	LU1C 0100	F03FS04590
250	3,2	2,2	70	22	4CH 21x5	LU1C 0200	F03FS04592
300	3,2	2,2	30	26	FT01	LU1C 0400	F03FS04595
300	3,2	2,2	35	26		LU1C 0500	F03FS04597
300	3,2	2,2	70	26	4CH 21x5	LU1C 0700	F03FS04599
315	3,2	2,2	30	28	FT01	LU1C 0800	F03FS04601
350	3,5	2,5	30	30	FT02	LU1C 1000	F03FS04603
350	3,5	2,5	35	30		LU1C 1100	F03FS04605
350	3,5	2,5	70	30	4CH 21x5	LU1C 1200	F03FS04607
400	4,0	2,8	30	34	2/10/60	LU1C 1300	F03FS04609
450	4,4	3,0	30	38	2/10/60	LU1C 1400	F03FS04611
500	4,4	3,2	30	42	2/10/60	LU1C 1500	F03FS04612
550	4,4	3,5	30	48	2/10/60	LU1C 1600	F03FS04613

GATECH
www.freud.rs

Cutting height - Visina materijala (mm)



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Ultimate Najbolja	High Odlična	Good Dобра
Ripping of softwood Uzdužno rezanje mekog drveta		
Ripping of hardwood Uzdužno rezanje tvrdog drveta		

LU1D



HW - Saw blades to cut solid wood TM - Testere za rezanje masiva

Saw blades suitable for ripping.

Machines: Table saws, multiripping machines.

Features: ATB 10° tooth with positive cutting angle.

Material: Soft, hard and exotic solid wood without loose knots.

Testere za uzdužno rezanje.

Mašine: Stabilni cirkulari, višelisni cirkulari.

Oblik zuba: ATB 10° sa pozitivnim uglom rezanja.

Materijal: Meko, tvrdo i egzotično drvo bez čvorova.


FT01: 2/7/42 + 2/9/46,4 + 2/10/60

FT02: 2/9/46,4 + 2/10/60


D mm	B mm	b mm	d mm	Z	NL - KN Pomoći otvori	Code Šifra	SAP SAP
250	3,2	2,2	30	24	FT01	LU1D 0100	F03FS04615
250	3,2	2,2	70	24	4CH 21x5	LU1D 0200	F03FS04617
300	3,2	2,2	30	28	FT01	LU1D 0500	F03FS04620
300	3,2	2,2	60	28	4CH 21x5	LU1D 0600	F03FS04622
300	3,2	2,2	70	28	4CH 21x5	LU1D 0800	F03FS04624
350	3,5	2,5	30	32	FT02	LU1D 1100	F03FS04628
350	3,5	2,5	70	32	4CH 21x5	LU1D 1000	F03FS04626

GATECH
www.freud.rs

HW H01K




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.


Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv


Ripping of softwood
Uzdužno rezanje mekog drveta
Ripping of hardwood
Uzdužno rezanje tvrdog drveta

Ultimate Najbolja	High Odlična	Good Dobra
●	●	●

LU1E




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades to cut solid wood - Thin kerf

TM - Testere za rezanje masiva - Uzak rez

Saw blades suitable for ripping. The reduced cutting height makes workpiece feeding easier.

Machines: Table saws, portable machines.

Features: Flat tooth with positive cutting angle and anti-kickback device.

Material: Soft and hard dried wood, also with loose knots.

Testere za uzdužno rezanje. Smanjena visina reza omogućava lakše ubacivanje komada.

Mašine: Stabilni cirkulari, ručni cirkulari.

Oblak zuba: Ravan sa pozitivnim uglom rezanja i sistemom protiv odskakanja.

Materijal: Meko i tvrdo suvo drvo, može i sa čvorovima.

FT01: 2/7/42 + 2/9/46,4 + 2/10/60

D	B	b	d	Z	NL	Code	Šifra	SAP	SAP
mm	mm	mm	mm		Pomoći otvori				
250	2,5	1,6	30	24	FT01	LU1E 0100	F03FS04630		
300	2,6	1,8	30	24		LU1E 0500	F03FS04638		
300	2,7	1,8	25	28		LU1E 0200	F03FS04632		
300	2,7	1,8	30	28	FT01	LU1E 0300	F03FS04634		
350	3,0	2,2	30	32	FT01	LU1E 0400	F03FS04636		

GATECH
www.freud.rs

Ultimate Najbolja	High Odlična	Good Dobra
Ripping of solid wood Uzdužno rezanje masiva		
Cross cutting of solid wood Poprečno rezanje masiva		
Wood composites Drveni kompoziti		

Ripping of solid wood


Uzdužno rezanje masiva

Cross cutting of solid wood


Poprečno rezanje masiva

Wood composites

Drveni kompoziti




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaju u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades to cut solid wood - Thin kerf TM- Testere za rezanje masiva - Uzak rez

Saw blades suitable for ripping. The reduced cutting height makes workpiece feeding easier.

Machines: Table saws, portable machines.

Features: ATB 10° tooth with positive cutting angle.

Material: Soft and hard dried wood, without loose knots.

Testere za uzdužno rezanje. Smanjena visina reza omogućava lakše ubacivanje komada.

Mašine: Stabilni cirkulari, ručni cirkulari.

Oblik zuba: ATB 10° sa pozitivnim uglom rezanja.

Materijal: Meko i tvrdo suvo drvo, bez čvorova.

FT01: 2/7/42 + 2/9/46,4 + 2/10/60


D mm	B mm	b mm	d mm	Z mm	NL Pomoći otvori	Code Šifra	SAP SAP
250	2,5	1,6	30	24	FT01	LU1F 0100	F03FS04640
300	2,7	1,8	30	28	FT01	LU1F 0200	F03FS04642
350	3,0	2,2	30	32	FT01	LU1F 0300	F03FS04644

GATECH
www.freud.rs


Ultimate Najbolja	High Odlična	Good Dobra
●	●	

Ripping of softwood
Uzdužno rezanje mekog drveta
Ripping of hardwood
Uzdužno rezanje tvrdog drveta

LU1G




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades to cut solid wood - rounded teeth on the side TM - Testere za rezanje masiva - ravan zub zaobljenih ivica

Saw blades suitable for ripping with fine cutting finish and without scratching, in order to achieve a perfectly smoothed surface.

Machines: Table saws.

Features: Straight tooth, rounded on the side, with positive cutting angle.

Material: Softwood.

Testere za uzdužno rezanje - za fini rez i završnu obradu bez grebanja.

Mašine: Stabilni cirkulari.

Oblik zuba: Ravan zub zaobljenih ivica, sa pozitivnim uglom rezanja.

Materijal: Meko drvo.

FT01: 2/7/42 + 2/9/46,4 + 2/10/60

D mm	B mm	b mm	d mm	Z mm	NL Pomoći otvori	Code Šifra	SAP SAP
250	3,0	2,0	30	40	FT01	LU1G 0100	F03FS04646
300	3,0	2,0	30	48	FT01	LU1G 0200	F03FS04647
350	3,2	2,2	30	60	FT01	LU1G 0300	F03FS04648

GATECH
www.freud.rs

Comparison between the cut of a conventional saw blade and a saw blade equipped with teeth that is rounded on the side.

Poređenje kvaliteta reza konvencionalne testere sa kvalitetom reza testere koja ima zub zaobljenih ivica.




Conventional saw blades
Konvencionalne testere




LU1G saw blades
LU1G testere

Ripping of softwood
Uzdužno rezanje mekog drveta

Ultimate Najbolja	High Odlična	Good Dobra




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades to cut solid wood - Thin kerf

TM - Testere za rezanje masiva - Uzak rez

Saw blades suitable for ripping and crosscutting. The reduced cutting height makes workpiece feeding easier.

Machines: Table saws, portable machines.

Features: ATB 15° tooth with positive cutting angle.

Material: Good quality, soft and hard solid wood.

Testere za uzdužno i poprečno rezanje. Smanjena visina reza omogućava lakše ubacivanje komada.

Mašine: Stabilni cirkulari, ručni cirkulari.


Oblik zuba: ATB 15° sa pozitivnim uglom rezanja.

Materijal: Kvalitetno meko i tvrdo drvo.

FT01: 2/7/42 + 2/9/46,4 + 2/10/60

D mm	B mm	b mm	d mm	Z	NL Pomoći otvori	Code Šifra	SAP SAP
180	1,5	1,0	30	40	2/7/42	LU1H 0100	F03FS04649
185	1,5	1,0	25,4	40		LU1H 0200	F03FS04650
200	1,5	1,0	30	40	2/7/42	LU1H 0300	F03FS07131
200	1,5	1,0	30	60	2/7/42	LU1H 0400	F03FS04651
205	1,5	1,0	25,4	40		LU1H 0500	F03FS04652
205	1,5	1,0	25,4	60		LU1H 0600	F03FS04653
250	2,5	1,6	30	48	FT01	LU1H 0700	F03FS04655
250	2,5	1,6	30	60	FT01	LU1H 0800	F03FS04657
250	2,8	2,0	30	30	2/10/60	LU1H 1500	F03FS04670
250	2,8	2,0	30	40	2/10/60	LU1H 1600	F03FS07127
300	2,8	2,0	30	36	FT01	LU1H 1400	F03FS04668
300	2,8	2,0	30	54	FT01	LU1H 0900	F03FS04659
300	2,8	2,0	35	54		LU1H 1000	F03FS04661
300	2,8	2,0	30	72	FT01	LU1H 1100	F03FS04663
350	3,0	2,2	30	60	FT01	LU1H 1200	F03FS04665
350	3,0	2,2	30	84	FT01	LU1H 1300	F03FS04667

GATECH
www.freud.rs




Ripping and crosscutting of softwood
Uzdužno i poprečno rezanje mekog drveta

Solid wood
Masiv


Ripping and crosscutting of hardwood
Uzdužno i poprečno rezanje tvrdog drveta

Wood composites
Drveni kompoziti

Ultimate Najbolja	High Odlična	Good Dobra
●	●	
●	●	
		●



Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.

HW - Saw blades to cut solid wood frames TM - Testere za rezanje ramova od masiva

Saw blades suitable for crosscutting. Without splintering frames and end trims of previously profiled items, where the items have to be coupled to perfectly match, even if they are covered with paint, chalk and other abrasive and fine materials.

Machines: Single or double-head miter saws.

Features: ATB 20° tooth with positive cutting angle.

Material: Soft and hardwood.

Testere za poprečno rezanje. Bez rastavljanja ramova i prethodnog pripremanja profila, kada je potrebno savršeno poklapanje, čak i u slučaju kada se na ramovima nalazi farba, kreda ili neki drugi abrazivni ili fini materijal.

Mašine: Obični ili dvoglavi gerovi.

Oblik zuba: ATB 20° sa pozitivnim uglom rezanja.

Materijal: Meko i tvrdo drvo.

FT02: 2/9/46,4 + 2/10/60

D mm	B mm	b mm	d mm	Z	NL Pomoći otvori	Code Šifra	SAP SAP
200	2,95	2,5	30	64	2/7/42	LU1I 0100	F03FS04673
250	2,95	2,5	20	80	2/6/32	LU1I 0200	F03FS04675
250	2,95	2,5	30	80	FT02	LU1I 0300	F03FS04677
250	2,95	2,5	30	96	FT02	LU1I 0400	F03FS04679
275	2,95	2,5	20	84	2/6/32	LU1I 0500	F03FS04681
300	2,95	2,5	30	96	FT02	LU1I 0600	F03FS04682
300	2,95	2,5	30	112	FT02	LU1I 0700	F03FS04684
330	3,45	3,0	30	96	FT02	LU1I 0800	F03FS04686
350	3,45	3,0	30	108	FT02	LU1I 0900	F03FS04688

GATECH
www.freud.rs



HW - Saw blades to cut solid wood frames

TM - Testere za rezanje ramova od masiva

Suitable for crosscutting. High-performance saw blades, with excellent cut and without splintering; finished and perfectly smooth surface, which is specifically recommended for frames' and profiles' end trims whose front-end cut keeps visible.

Machines: Single or double-head miter saws.

Features: Flat - ATB 10° tooth with axial 15° and positive cutting angle.

Material: Soft and hardwood.

Testere za poprečno rezanje. Testere vrhunskih performansi, sa odličnim kvalitetom reza bez cepanja ramova; završni rez je savršeno gladak, što je posebno važno kod ramova kod kojih je prednji deo reza vidljiv.

Mašine: Obični ili dvoglavi gerovi.

Oblik zuba: ATB 10° Zub sa aksijalnim 15° i pozitivnim uglom rezanja.

Materijal: Meko i tvrdo drvo.

FT01: 2/7/42 + 2/9/46,4 + 2/10/60

D mm	B mm	b mm	d mm	z	NL Pomoći otvori	Code Šifra	SAP SAP
250	3,0	2,2	30	100	FT01	LU1L 0100	F03FS04690
250	3,0	2,2	30	120	FT01	LU1L 0200	F03FS04691
255	3,0	2,2	25,4	100		LU1L 0300	F03FS04692
255	3,0	2,2	25,4	120		LU1L 0400	F03FS04693
300	3,0	2,2	30	100	FT01	LU1L 0500	F03FS04694
300	3,0	2,2	30	120	FT01	LU1L 0600	F03FS04695
305	3,0	2,2	25,4	100		LU1L 0700	F03FS04696
305	3,0	2,2	25,4	120		LU1L 0800	F03FS04697
305	3,0	2,2	30	100		LU1L 1100	F03FS06410
350	3,0	2,2	30	120	FT01	LU1L 0900	F03FS04698
355	3,0	2,2	25,4	120		LU1L 1000	F03FS04699

GATECH
www.freud.rs




Anti-vibration




Silver LCE Coating



HW HOOK



Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.


Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.

Frames Ramovi	Ultimate Najbolja	High Odlična	Good Dobra


LG1C



HW H01K




Tooth features - Karakteristike zuba



Minimum and maximum RPM based on the blade diameter.

Minimalan i maksimalan broj obrtaja u odnosu na prečnik testere.



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Solid wood
Masiv

HW - Saw blades to cut solid wood

TM - Testere za rezanje masiva

Saw blades suitable for ripping.

Machines: Table saws, multiripping machines.

Features: ATB 10° tooth with positive cutting angle.

Material: Soft and hard solid wood, also with loose knots.

Testere za uzdužno rezanje masiva.

Mašine: Stabilni cirkulari, višelisni cirkulari.

Oblik zuba: ATB 10° sa pozitivnim uglom rezanja.

Materijal: Meko i tvrdo drvo (masiv), može i sa čvorovima.


FT01: 2/7/42 + 2/9/46,4 + 2/10/60

FT02: 2/9/46,4 + 2/10/60

D	B	b	d	Z	NL	Code	SAP
mm	mm	mm	mm		Pomoći otvori	Šifra	SAP
250	3,2	2,2	30	22	FT01		LG1C 0100 F03FS07559
300	3,2	2,2	30	26	FT01		LG1C 0400 F03FS07560
350	3,5	2,5	30	30	FT02		LG1C 1000 F03FS07561

GATECH
www.freud.rs

Cutting height - Visina materijala (mm)



Maximum depth of cut based on the blade diameter.
Maksimalna visina materijala koji se reže u odnosu na prečnik testere.

Ultimate Najbolja	High Odlična	Good Dobra
Ripping of softwood Uzdužno rezanje mekog drveta		
Ripping of hardwood Uzdužno rezanje tvrdog drveta		

Table 1

Tabela 1

Saw blade's technical table to obtain the correct saw blade diameter based on its tip speed and the material to cut
Tabela za određivanje optimalnog prečnika testere prema perifernoj brzini i vrsti materijala za obradu

GATECH
www.freud.rs

D (mm)

Saw blade diameter
Prečnik testere

Tip speed (m/s) Periferna brzina u m/s	Recommended for Preporučuje se za
50 - 90	Softwood / Meko drvo
50 - 80	Hardwood / Tvrdo drvo
50 - 85	Exotic wood / Egzotično drvo
60 - 80	Chipboard / Iverica
60 - 80	Joinery wood / Panel ploče
30 - 60	MDF / Medijapan (MDF)
40 - 60	Laminated and bilaminated / Oplemenjeni materijali





Table 2

Tabela 2



Saw blade's technical table to obtain the correct tooth feed rate, the feed rate of the material, the number of teeth and the RPM
 Tabela za određivanje adekvatne brzine zuba, brzine ubacivanja komada, broja zuba i broja obrtaja (RPM)



GA TECH
www.freud.rs

Explanation of symbols and abbreviations

Pojašnjenje simbola i skraćenica



Explanation of symbols and abbreviations

Pojašnjenje simbola i skraćenica

PERFORMANCE		
Ultimate Najbolja	High Odlična	Standard Dobra
●	●	●

CHART ABOUT THE SAW BLADE'S
PERFORMANCE
TABELA PERFORMANSI TESTERA

GATECH
www.freud.rs

SYMBOLS TO READ THE PRODUCT TABLES SIMBOLI POTREBNI ZA TUMAČENJE TABELA PROIZVODA

D	Diameter Prečnik	d	Central bore Centralni otvor	α	Hook angle Grudni ugao
B	Cutting thickness Debljina reza	Z	Number of teeth Broj zuba	β	Back relief angle Leđni ugao
B-B1	Adjustable cutting thickness Podesiva debljina reza	KN CH	Keyways Otvori za klinove	Code Codice	Item code Šifra artikla
b	Saw blade body thickness Debljina tela testere	NL FT	Pin holes Pomoći otvori	SAP SAP	Item code - for SAP users only Šifra artikla - samo za klijente SAP

OTHER SYMBOLS ALTRI SIMBOLI






	Silver I.C.E. Coating Silver I.C.E. zaštitni sloj		Multi-rip saw blade for ripping of softwood Testera za uzdužno rezanje mekog drveta na višelisnim cirkularima		Saw blade to cut solid wood and composites with nails and impurities Testera za rezanje masiva i kompozita sa ekserima i nečistoćama
	Perma-SHIELD coating Perma-SHIELD zaštitni sloj		Multi-rip saw blade for ripping of hardwood Testera za uzdužno rezanje tvrdog drveta na višelisnim cirkularima		Saw blade to cut laminates Testera za rezanje laminata
	Anti-vibration technology Antivibraciona tehnologija		Saw blade for ripping of softwood Testera za uzdužno rezanje mekog drveta		Saw blade to cut veneered Testera za rezanje furnira
	Saw blade for miter saws Testera za ger		Saw blade for ripping of hardwood Testera za uzdužno rezanje tvrdog drveta		Scoring saw blade Predrezač
	Saw blade for portable machines Testera za prenosne cirkulare		Saw blade for ripping of softwood Testera za uzdužno rezanje mekog drveta		Saw blade to cut picture frames Testera za rezanje ramova
	Right hand or left hand Desni ili levi smer kretanja		Saw blade for ripping of hardwood Testera za uzdužno rezanje tvrdog drveta		Saw blade to cut PVC Testera za rezanje PVC-a
	Tools for automatic feed Alati za automatsko dodavanje		Saw blade for cross cutting of softwood Testera za poprečno rezanje mekog drveta		Saw blade to cut plastic materials Testera za rezanje plastičnih materijala
	Disposable knives Izmenjive pločice (nožići)		Saw blade for cross cutting of hardwood Testera za poprečno rezanje tvrdog drveta		Saw blade to cut plexiglas Testera za rezanje pleksiglasa
			Saw blade for ripping and cross cutting of softwood Testera za uzdužno i poprečno rezanje mekog drveta		Saw blade to cut solid surfaces Testera za rezanje radnih ploča
			Saw blade for ripping and cross cutting of hardwood Testera za uzdužno i poprečno rezanje mekog drveta		Saw blade to cut non-ferrous metals Testera za rezanje aluminijuma i obojenih metala
			Saw blade to cut wood composites Testera za rezanje drvenih kompozita		Saw blade to cut ferrous metals Testera za rezanje gvožđa i crnih metala

Tips for the correct use of a saw blade

Saveti za ispravno korišćenje testere

Tips for the correct use of a saw blade

Saveti za ispravno korišćenje testere



To obtain the best performance from a saw blade we suggest to follow these simple instructions:

- The machine must be in good condition, free of vibrations.
- The flanges used to secure the blade must be of the same diameter, at least 1/3 of the blade's diameter (Fig. 1).
- The flanges must be parallel to each other. Also check tolerances on diameters, sides and concentricity, by using a clock gauge (Fig. 2).
- The spacers must be perfectly parallel (Fig. 2).
- The spindle must be perfectly straight and with an H7 tolerance (Fig. 3).
- After continuous use, remove the blade and clean it with the appropriate solvents making sure to get rid of built up resin. For the synthetic coated (perma-SHIELD) blades, it's sufficient to use warm water. In any case, avoid using solvents containing caustic soda.
- The blades must be sharpened as soon as they become dull, maintaining the original tooth angles.
- For sharpening, always use the correct grinding wheels and plenty of cooling liquid.
- Always keep spacers and flanges clean.
- When sharpening, the shoulder of the teeth must not be lowered more than needed. This operation must be done with appropriate precision machinery and never by hand. There is the risk of breaking the tip or upsetting the blade balance (Fig. 4 - 5).
- On ripping machines, the feeding track must be levelled with the fixed table.
- Before starting the cut of the material, make sure the blade is correctly locked according to the machine's specifications.

Da biste iskoristili najbolje performanse testere, predlažemo Vam da pratite ova jednostavna uputstva:

- Mašina na kojoj radite mora biti u dobrom stanju, bez vibracija.
- Flanšne kojima se steže testera moraju biti istih dimenzija, otprilike minimum 1/3 prečnika testere (Slika 1).
- Flanšne za stezanje moraju biti paralelno postavljene. Proverite da li su dobro postavljene i pričvršćene pre započinjanja radova (Slika 2).
- Distantni prstenovi moraju biti savršeno paralelni (Slika 2)
- Osovina mora biti ravna i u toleranciji h7 (Slika 3).
- Nakon duže upotrebe, skinite testeru sa mašine i operite je odgovarajućim sredstvom da biste sprečili nagomilavanje otpadaka po njoj. Za testere sa sintetičkom (perma-SHIELD) prevlakom, dovoljno je da upotrebite toplu vodu. U svakom slučaju, izbegavajte upotrebu rastvora koji u sebi sadrže kaustičnu sodu.
- Naoštrite testere čim primetite da su tipe, zadržavajući originalne uglove zuba.
- Prilikom oštrenja uvek koristite odgovarajuće brusne ploče i dovoljno tečnosti za rashlađivanje.
- Vodite računa da distantni prstenovi i prirubnice budu uvek čisti.
- Telo iza zuba ne sme se spuštati više nego što je potrebno i to se nikada ne sme raditi ručno, jer postoji opasnost od lomljenja vrha i gubitka pravilnog balansa testere (Slike 4 - 5)
- Na višelisnim cirkularima, vučni valjci moraju biti u ravni sa fiksnim delom stola.
- Pre početka rezanja proverite da li je testera dobro fiksirana u skladu sa specifikacijama mašine.

GATECH
www.freud.rs

Tips for the correct use of a saw blade

Saveti za ispravno korišćenje testere




Table 1 - Tabela 1

Saw blade diameter Prečnik testere	Maximum RPM Max OBRTAJA/MIN
100 mm	23.000
125 mm	18.000
150 mm	14.500
180 mm	11.500
185 mm	11.000
200 mm	10.000
225 mm	8.500
250 mm	8.000
255 mm	7.800
280 mm	7.100
300 mm	6.500
320 mm	6.000
350 mm	5.500
380 mm	5.000
400 mm	4.700
430 mm	4.400
450 mm	4.200
500 mm	3.750
550 mm	3.400
600 mm	3.100
630 mm	2.950
650 mm	2.800
700 mm	2.600
730 mm	2.500
760 mm	2.400
800 mm	2.250

Not valid for saw blades to cut ferrous metals.
Nije validno za testere za rezanje gvožđa i crnih metala.

SAW BLADE ALIGNMENT ON A TABLE SAW

- If the saw blade and the saw are not correctly aligned to the table and the fence, then there is the possibility that a serious accident may occur (for example, violent kickbacks) or that the workpiece may scorch or splinter. The first thing you must do is read the instruction sheet carefully. This is necessary so as you may acquire the understanding and comprehension of the corrections suggested in this section.
- Before carrying out the following instructions, make sure that the starter switch is off and that the machine is not connected to the socket.

Mounting the saw blade onto the table:

We advise you to use precise measuring instruments when mounting your saw blade. Clean the saw blade well, before mounting it onto the machine. Mount the saw blade onto the arbor. Adjust the arbor to its maximum height. With the aid of the most precise measuring instrument available, verify that the saw blade is parallel to the miter gauge slots (Fig. 6). Adjust as needed. This step is necessary to obtain crosscuts with the maximum in quality finish and for setting up the fence for ripping.

Positioning the fence for ripping:

After having positioned the saw blade so as it is parallel to the miter gauge slots, you may proceed with setting the fence. The fence should ideally be parallel to the saw blade. However since it is impossible to position the guide "exactly" it is necessary to leave a slight margin of clearance on the exit side of the cut so as to avoid the wood becoming wedged in between the fence and the saw blade.

Adjust the fence so as when it is aligned to the miter gauge slots, there is a space of 0,1 mm (fig. 7; for the correct adjustment, consult the machine's instruction manual).

- The maximum RPM of a circular saw blade varies according the diameter of the blade itself (table 1). If you exceed this limit, the saw blade will lose its characteristics, therefore influencing the cutting quality and the work life of the blade itself, not to mention the dangers implied to the user who may incur serious injury.
- The saw blade's projection (T) with respect to the workpiece must be at least equal to the height of the blade's tooth (fig. 8). Increase or decrease the projection of the saw blade to improve the quality of the cutting finish.
- The number of teeth cutting (teeth cutting the wood simultaneously - fig. 9) must be between 3 or 4. With less than three teeth cutting, the saw blade begins to vibrate leading to an uneven cut. If you want to cut workpieces with increased thicknesses (S - fig. 11), but wish to maintain the same diameter saw blade, then use a blade with less teeth. If instead you want to cut workpieces with a reduced thickness, but also maintain the same diameter saw blade, then use a blade with more teeth.

POSTAVLJANJE TESTERE NA MAŠINU

• Ukoliko testere i mašina nisu pravilno postavljene u odnosu na sto i vođicu, može doći do ozbiljnih nezgoda (npr. odskakanja komada) ili se komad može oštetiti. Prva stvar koju morate uraditi jeste da pažljivo pročitate uputstvo za rukovanje mašinom. Zahvaljujući tome, moći ćete i da razumete i primenite savete koje Vam u ovom delu kataloga dajemo.

• Pre primene saveta koje Vam dajemo, proverite da li je mašina isključena i da nema dovoda struje.

Postavljanje testere na sto:

• Savetujemo Vam da koristite tačne merne instrumente kada postavljate testeru. Pre postavljanja, testera koja je radila dobro očistite. Postavite testeru na osovinu i dovedite je na maksimalnu visinu. Uz pomoć preciznog mernog instrumenta proverite da li je testera paralelna sa kliznim utorima (Slika 6). Podesite je na taj način. Ovaj korak je neophodan da bi se dobili poprečni rezovi maksimalnog kvaliteta završnog reza i da bi se postavila vođica za uzdužan rez.

Postavljanje vođice za poprečan rez:

• Kada ste postavili testeru paralelno sa kliznim utorima, možete pristupiti podešavanju vođice. Vođica bi u idealnim uslovima trebalo da bude paralelna sa testerom. Međutim, kako je nemoguće postaviti vođicu „apsolutno tačno“, potrebno je ostaviti malu marginu na izlaznoj strani reza da bi se izbeglo zaglavljivanje komada između vođice i testere. Podesite vođicu tako da bude otprilike oko 0,1mm između nje i kliznih utora (Slika 7). Za tačno podešavanje, pogledajte uputstvo koje ste dobili uz mašinu.


• Maksimalan broj obrtaja testere (RPM) zavisi od prečnika testere (Tabela 1). Ukoliko se ove vrednosti pređu, testera će izgubiti svoja svojstva, što će direktno uticati na kvalitet reza i vek trajanja testere – da ne spominjemo i opasnost od povreda koje se mogu desiti ukoliko se testera ošteći.

• Projekcija testere (T) mora biti takva da ona bude viša (viri iz materijala) barem za visinu zuba (Slika 8). Smanjenje ili povećanje te visine utiče na kvalitet završnog reza.

• Broj zuba koji se istovremeno nalaze u zahvatu (Slika 9) mora biti između 3 i 4. Ukoliko istovremeno kroz komad prodire manje od 3 zuba, testera počinje da vibrira i doći će do neravnomernog rezanja. Ukoliko želite da režete komad povećane visine (S – Slika 11), ali želite da zadržite istu dimenziju testere, koristite testere sa manjim brojem zuba. Ukoliko želite da režete komad manje visine, uz zadržavanje iste dimenzije testere, odlučite se za tetesu sa većim brojem zuba.

Tips for the correct use of a saw blade

Saveti za ispravno korišćenje testere



- To obtain the pitch (**P**) of a blade (the distance between teeth: fig. 10 - (see formula "a") multiply the thickness of the workpiece by 1,4142 and divide by 3 (if you want 3 teeth cutting) or by 4 (if you want 4 teeth cutting).
- Formula "b": to obtain the number of teeth (**Z**) of the saw blade, multiply the diameter (**D**) of the saw blade by 3,14 (π) and divide by the pitch of the saw blade - obtained from the previous formula. The shorter formula "c" allows you to obtain the nr. of the saw blade's teeth, knowing its diameter and the thickness of the workpiece.
- Korak (**P**) je udaljenost između zuba (Sl. 10). Da biste ga dobili (vidi formulu "a"), pomnožite debljinu komada sa 1,4142 i podelite s 3 (ako želite 3 zuba u zahvatu) ili 4 (ako želite 4 zuba u zahvatu).
- Formula "b": za dobijanje broja zuba (**Z**) testere, pomnožite njen prečnik (**D**) s 3,14 (π) i podelite s korakom (**P**) dobijenim u prethodnoj formuli. Kraća formula "c" omogućava da se dobije potreban broj zuba testere koristeći samo njen prečnik i debljinu komada koji se reže.

Formula A	Formula B	Formula C
$P = \frac{S \times 1,4142}{3}$	$Z = \frac{D \times 3,14}{P}$	$Z = \frac{D \times 8}{S}$

KEY:

LEGENDA:

P=pitch / korak

S=thickness of the workpiece / debljina komada

Z=nr. teeth of the saw blade / broj zuba testere

D=diameter of the saw blade / prečnik testere

ATTENTION:

These formulas are valid for crosscutting and cutting other wood composites of (MDF, plywood, chipboard and laminated panels) and cannot be applied for ripping.






PAŽNJA:

Ove formule su validne za poprečno rezanje drveta i pločastih materijala (medijapana MDF, iverice, šper ploče i laminata) i ne mogu se primeniti na uzdužno rezanje.

GATECH
www.freud.rs

Tips for the correct use of a saw blade

Saveti za ispravno korišćenje testere



- Rakers (Fig. 12) are inserts in HW that are brazed onto saw blades exclusively for cutting wood. They help keep a distance between the saw blade body and the workpiece, in order to avoid friction and overheating which cause the blade to deform.
- On saw blades for multiripping machines the anti kick-back device is advised in cases where wood has loose knots and discards cases insert themselves underneath the saw blade.
- The pairing of blade and arbor with keyways is excellent in all cases where the keyways are the same (Fig. 13) or smaller than the blade slots (Fig. 14).
- On machines with an arbor with 1 keyway, you can only mount blades with 1 keyway slot (Fig. 15); on machines with an arbor with 2 keyways, you can only mount blades with 2 or 4 keyway slots (Fig. 16).
- You cannot mount a saw blade with 2 keyways on an arbor with 1 keyway slot, because the pairing will not be balanced.
- In case multiripping saw blades are used, it is recommendable to assemble them with alternate keyways (Fig. 17).
- Shoulder blade ensures correct distribution of lateral forces created by crooked planks in heavy duty use. The shoulder blade must be the first blade on the guide side of the multiripping machine.
- Always use shoulder blade with the set of multiripping blades (Fig. 18).
- On multiripping saw blades, the thickness of the workpiece (S) varies according to the diameter of the blade (\varnothing) and the minimum diameter (\varnothing_1) of the rakers (the rakers position may vary from blade to blade - Fig. 19).

- Čistači (Slika 12) su TM pločice koje su lemljene na telo testera isključivo za rezanje drveta. Koriste se za odvajanje drveta od tela alata, kako bi se izbeglo trenje i pregrevanje što uzrokuje deformaciju testere.
- Na testerama za višelisne cirkulare, preporučuje se upotreba stezača protiv odskakanja komada, posebno u slučajevima kada drvo ima čvorove i kada se može desiti da ostaci komada koji se reže upadnu ispod testere.
- Pričvršćivanje testera za osovinu najbolje je kada postoje otvori koji odgovaraju dimenzijama klinova (Slika 13) ili su malo veći od dimenzija klinova (Slika 14).
- Na mašine čija osovina ima jedan klin mogu se montirati samo testere koji imaju jedan otvor za klin (Slika 15), a na mašine čija osovina ima dva kлина mogu se montirati testere koji imaju dva ili četiri otvora za klinove (Slika 16).
- Testera sa dva otvora za klin ne može se montirati na osovinu sa jednim klinom, jer ne bi mogla dobro da se balansira.
- Ukoliko se vrši postavljanje više testera za višelisne cirkulare odjednom, preporuka je da se to radi tako što će se svaka od testera pomeriti za po jedan otvor u odnosu na prethodnu (Slika 17).
- Krajnja testera na višelisnim cirkularima mora biti jača od ostalih i postavlja se kao prva na ulaznoj strani komada. Ona osigurava pravilnu distribuciju lateralnih sila prilikom obrade komada.
- Uvek koristite krajnju testeru u setu testera za višelisni cirkular (Slika 18).
- Kada su u pitanju višelisni cirkulari, debljina komada (S) zavisi od prečnika testere (\varnothing) i minimalnog prečnika (\varnothing_1) čistača (njihov položaj može varirati od testere do testere (Slika 19).

GATECH
www.freud.rs